

POWER SAW WITH IMPROVED SAFETY SYSTEM

Cross-Reference to Related Applications

5 This application is a continuation-in-part of the following U.S. Patent Applications, all of which are hereby incorporated by reference: Serial No. 09/676,190, filed September 29, 2000, Serial No. 09/929,221, filed August 13, 2001, Serial No. 09/929,226, filed August 13, 2001, Serial No. 09/929,227, filed August 13, 2001, Serial No. 09/929,234, filed August 13, 2001, Serial No. 09/929,235, filed August 13, 2001, Serial No. 09/929,236, filed August 13, 2001, Serial No. 09/929,237, filed August 13, 2001, Serial No. 09/929,238, filed August 13, 2001, Serial No. 09/929,240, filed August 13, 2001, Serial No. 09/929,241, filed August 13, 2001, Serial No. 09/929,242, filed August 13, 2001, Serial No. 09/929,244, filed August 13, 2001, Serial No. 09/929,425, filed August 13, 2001, and Serial No. 09/929,426, filed August 13, 2001.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015

on the base beneath the upraised blade and then bringing the blade down via the pivot arm to cut the workpiece. Miter saws present a risk of injury to users because the spinning blade is often exposed when in use. Furthermore, users often use their hands to position and support workpieces beneath the blade, which increases the chance that an injury will occur.

5 The present invention provides a miter saw with an improved safety system that is adapted to detect the occurrence of one or more dangerous, or triggering, conditions during use of the miter saw, such as when a user's body contacts the spinning saw blade. When such a condition occurs, the safety system is actuated to limit or even prevent injury to the user. The present invention is also adaptable for use with other power saws as well.

Brief Description of the Drawings

Fig. 1 is a schematic block diagram of a miter saw with a fast-acting safety system according to the present invention.

Fig. 2 is a schematic diagram of an exemplary safety system configured to stop the miter saw blade.

Fig. 3 is a schematic side elevation view of a miter saw having an alternative exemplary safety system configured to stop the miter saw pivot arm as well as the blade.

Fig. 4 is a magnified side view of an exemplary retraction assembly according to the present invention.

Fig. 5 is a magnified cross-sectional view of the retraction assembly of Fig. 4.

20 Fig. 6 is a magnified, fragmentary view of the retraction assembly of Fig. 4, showing the restraining mechanism in detail.

Fig. 7 is similar to Fig. 5 except that the clamping device is shown pivoted to the locked position.

Fig. 8 is similar to Fig. 7 except that the housing is shown pushed upward relative to the brace member. For clarity, the components of the restraining member are not shown.

Fig. 9 is a schematic side elevation view of a radial arm saw having an alternative exemplary safety system configured to retract and stop the blade.

5 Fig. 10 is a schematic side elevation view of a pneumatic up-cut chop saw having an alternative exemplary safety system configured to retract the blade.

Detailed Description and Best Mode of the Invention

A miter saw according to the present invention is shown schematically in Fig. 1 and indicated generally at 10. Miter saw 10 may be any of a variety of different types and configurations of miter saw adapted for cutting workpieces, such as wood, plastic, etc. Miter saw 10 includes an operative structure 12 having a cutting tool 14 and a motor assembly 16 adapted to drive the cutting tool. Miter saw 10 also includes a safety system 18 configured to minimize the potential of a serious injury to a person using miter saw 10. Safety system 18 is adapted to detect the occurrence of one or more dangerous, or triggering, conditions during use of miter saw 10. If such a dangerous condition is detected, safety system 18 is adapted to engage operative structure 12 to limit any injury to the user caused by the dangerous condition.

Miter saw 10 also includes a suitable power source 20 to provide power to operative structure 12 and safety system 18. Power source 20 may be an external power source such as line current, or an internal power source such as a battery. Alternatively, power source 20 may include a combination of both external and internal power sources. Furthermore, power source 20 may include two or more separate power sources, each adapted to power different portions of miter saw 10.

It will be appreciated that operative structure 12 may take any one of many different forms, depending on the type of miter saw 10. As will be described in more detail below, operative structure 12 typically takes the form of an arm pivotally coupled to a base. Cutting tool 14 is mounted on the arm and pivotal toward a workpiece supported by the base.

5 Alternatively, the arm may be both pivotally and slidably coupled to the base.

Motor assembly 16 includes one or more motors adapted to drive cutting tool 14. The motors may be either directly or indirectly coupled to the cutting tool. Typically, motor assembly 16 is mounted on the pivot arm and directly coupled to the cutting tool.

Safety system 18 includes a detection subsystem 22, a reaction subsystem 24 and a control subsystem 26. Control subsystem 26 may be adapted to receive inputs from a variety of sources including detection subsystem 22, reaction subsystem 24, operative structure 12 and motor assembly 16. The control subsystem may also include one or more sensors adapted to monitor selected parameters of miter saw 10. In addition, control subsystem 26 typically includes one or more instruments operable by a user to control the miter saw. The control subsystem is configured to control miter saw 10 in response to the inputs it receives.

Detection subsystem 22 is configured to detect one or more dangerous, or triggering, conditions during use of miter saw 10. For example, the detection subsystem may be configured to detect that a portion of the user's body is dangerously close to, or in contact with, a portion of cutting tool 14. As another example, the detection subsystem may be configured to detect the rapid movement of a workpiece due to kickback by the cutting tool, as is described in U.S. Provisional Patent Application Serial No. 60/182,866, filed February 16, 2000 and U.S. Patent Application Serial No. 09/676,190, filed September 29, 2000, the disclosures of which are herein incorporated by reference. In some embodiments, detection subsystem 22 may inform control

subsystem 26 of the dangerous condition, which then activates reaction subsystem 24. In other embodiments, the detection subsystem may be adapted to activate the reaction subsystem directly.

Once activated in response to a dangerous condition, reaction subsystem 24 is configured to engage operative structure 12 quickly to prevent serious injury to the user. It will be appreciated that the particular action to be taken by reaction subsystem 24 will vary depending on the type of miter saw 10 and/or the dangerous condition that is detected. For example, reaction subsystem 24 may be configured to do one or more of the following: stop the movement of cutting tool 14, disconnect motor assembly 16 from power source 20, place a barrier between the cutting tool and the user, or retract the cutting tool from its operating position, etc. The reaction subsystem may be configured to take a combination of steps to protect the user from serious injury. Placement of a barrier between the cutting tool and teeth is described in more detail in U.S. Provisional Patent Application Serial No. 60/225,206, filed August 14, 2000 and U.S. Patent Application Serial No. 09/929,226, filed August 13, 2001, the disclosures of which are herein incorporated by reference. Retraction of the cutting tool from its operating position is described in more detail in U.S. Provisional Patent Application Serial No. 60/225,089, filed August 14, 2000 and U.S. Patent Application Serial No. 09/929,242, filed August 13, 2001, the disclosures of which are herein incorporated by reference.

The configuration of reaction subsystem 24 typically will vary depending on which action(s) are taken. In the exemplary embodiment depicted in Fig. 1, reaction subsystem 24 is configured to stop the movement of cutting tool 14 and includes a brake mechanism 28, a biasing mechanism 30, a restraining mechanism 32, and a release mechanism 34. Brake mechanism 28 is adapted to engage operative structure 12 under the urging of biasing mechanism 30. During

normal operation of miter saw 10, restraining mechanism 32 holds the brake mechanism out of engagement with the operative structure. However, upon receipt of an activation signal by reaction subsystem 24, the brake mechanism is released from the restraining mechanism by release mechanism 34, whereupon, the brake mechanism quickly engages at least a portion of the operative structure to bring the cutting tool to a stop.

It will be appreciated by those of skill in the art that the exemplary embodiment depicted in Fig. 1 and described above may be implemented in a variety of ways depending on the type and configuration of operative structure 12. Turning attention to Fig. 2, one example of the many possible implementations of miter saw 10 includes a cutting tool 14 in the form of a circular blade 40 mounted on a rotating shaft or arbor 42. Blade 40 includes a plurality of cutting teeth (not shown) disposed around the outer edge of the blade. As described in more detail below, braking mechanism 28 is adapted to engage the teeth of blade 40 and stop the rotation of the blade.

In the exemplary implementation, detection subsystem 22 is adapted to detect the dangerous condition of the user coming into contact with blade 40. The detection subsystem includes a sensor assembly, such as contact detection plates 44 and 46, capacitively coupled to blade 40 to detect any contact between the user's body and the blade. Typically, the blade, or some larger portion of cutting tool 14 is electrically isolated from the remainder of miter saw 10. Alternatively, detection subsystem 22 may include a different sensor assembly configured to detect contact in other ways, such as optically, resistively, etc. In any event, the detection subsystem is adapted to transmit a signal to control subsystem 26 when contact between the user and the blade is detected. Various exemplary embodiments and implementations of detection subsystem 22 are described in more detail in U.S. Provisional Patent Application Serial

No. 60/225,200, filed August 14, 2000, U.S. Patent Application Serial No. 09/929,426, filed August 13, 2001, U.S. Provisional Patent Application Serial No. 60/225,211, filed August 14, 2000, U.S. Patent Application Serial No. 09/929,221, filed August 13, 2001, and U.S. Provisional Patent Application Serial No. 60/270,011, filed February 20, 2001, the disclosures of which are herein incorporated by reference.

Control subsystem 26 includes one or more instruments 48 that are operable by a user to control the motion of blade 40. Instruments 48 may include start/stop switches, speed controls, direction controls, etc. Control subsystem 26 also includes a logic controller 50 connected to receive the user's inputs via instruments 48. Logic controller 50 is also connected to receive a contact detection signal from detection subsystem 22. Further, the logic controller may be configured to receive inputs from other sources (not shown) such as blade motion sensors, workpiece sensors, etc. In any event, the logic controller is configured to control operative structure 12 in response to the user's inputs through instruments 48. However, upon receipt of a contact detection signal from detection subsystem 22, the logic controller overrides the control inputs from the user and activates reaction subsystem 24 to stop the motion of the blade. Various exemplary embodiments and implementations of control subsystem 26 are described in more detail in U.S. Provisional Patent Application Serial No. 60/225,059, filed August 14, 2000, U.S. Patent Application Serial No. 09/929,237, filed August 13, 2001, U.S. Provisional Patent Application Serial No. 60/225,094, filed August 14, 2000 and U.S. Patent Application Serial No. 09/929,234, filed August 13, 2001, the disclosures of which are herein incorporated by reference.

In the exemplary implementation shown in Fig. 2, brake mechanism 28 includes a pawl 60 mounted adjacent the edge of blade 40 and selectively moveable to engage and grip the teeth

of the blade. Pawl 60 may be constructed of any suitable material adapted to engage and stop the blade. As one example, the pawl may be constructed of a relatively high strength thermoplastic material such as polycarbonate, ultrahigh molecular weight polyethylene (UHMW) or Acrylonitrile Butadiene Styrene (ABS), etc., or a metal such as aluminum, etc. It will be appreciated that the construction of pawl 60 will vary depending on the configuration of blade 40. In any event, the pawl is urged into the blade by a biasing mechanism such as a spring 66. In the illustrative embodiment shown in Fig. 2, pawl 60 is pivoted into the teeth of blade 40. It should be understood that sliding or rotary movement of pawl 60 may also be used. The spring is adapted to urge pawl 60 into the teeth of the blade with sufficient force to grip the blade and quickly bring it to a stop.

The pawl is held away from the edge of the blade by a restraining mechanism such as a fusible member 70. The fusible member is constructed of a suitable material adapted to restrain the pawl against the bias of spring 66, and also adapted to melt under a determined electrical current density. Examples of suitable materials for fusible member 70 include NiChrome wire, stainless steel wire, etc. The fusible member is connected between the pawl and a contact mount 72. Preferably member 70 holds the pawl relatively close to the edge of the blade to reduce the distance pawl 60 must travel to engage blade 40. Positioning the pawl relatively close to the edge of the blade reduces the time required for the pawl to engage and stop the blade. Typically, the pawl is held approximately 1/32-inch to 1/4-inch from the edge of the blade by fusible member 70; however other pawl-to-blade spacings may also be used within the scope of the invention.

Pawl 60 is released from its unactuated, or cocked, position to engage blade 40 by a release mechanism in the form of a firing subsystem 76. The firing subsystem is coupled to

contact mount 72, and is configured to melt fusible member 70 by passing a surge of electrical current through the fusible member. Firing subsystem 76 is coupled to logic controller 50 and activated by a signal from the logic controller. When the logic controller receives a contact detection signal from detection subsystem 22, the logic controller sends an activation signal to firing subsystem 76, which melts fusible member 70, thereby releasing the pawl to stop the blade. Various exemplary embodiments and implementations of reaction subsystem 24 are described in more detail in U.S. Provisional Patent Application Serial No. 60/225,056, filed August 14, 2000, U.S. Patent Application Serial No. 09/929,240, filed August 13, 2001, U.S. Provisional Patent Application Serial No. 60/225,170, filed August 14, 2000, U.S. Patent Application Serial No. 09/929,227, filed August 13, 2001, U.S. Provisional Patent Application Serial No. 60/225,169, filed August 14, 2000, U.S. Patent Application Serial No. 09/929,241, filed August 13, 2001, the disclosures of which are herein incorporated by reference.

In the exemplary embodiment illustrated in Fig. 2, reaction subsystem 24 is configured to act on cutting tool 14 and stop the rotation of blade 40. As mentioned above, reaction subsystem 24 additionally or alternatively may be configured to act on a different portion of operative structure 12 to stop and/or reverse the translation of blade 40 toward the workpiece and the user's body. For example, it may be desirable to stop the downward movement of the pivot arm that supports the blade. Those of skill in the art will appreciate that when the rotation of blade 40 is stopped suddenly, the angular momentum of the blade may be transferred to pivot arm 98, causing the pivot arm to move downward toward base assembly 90 and the user. Thus, it may be desirable to stop the movement of the pivot arm at substantially the same time the movement of the blade is stopped. Alternatively, the movement of the pivot arm may be stopped without stopping the rotation of the blade. A variety of different safety systems configured to stop the

downward movement of the pivot arm are described in U.S. Provisional Patent Application Serial No. 60/270,942, filed February 22, 2001, the disclosure of which is herein incorporated by reference.

In addition to stopping the movement of the pivot arm, it may also be desirable to quickly reverse the movement to retract the pivot arm upward away from the workpiece and the user's body. Alternatively, reaction subsystem 24 may be configured to retract a different portion of operative structure 12 instead of, or in addition to, the pivot arm. The reaction subsystem is configured to retract the pivot arm or other portion quickly enough to prevent serious injury to the user. Where the reaction subsystem is triggered in response to contact between the user's body and the blade, the reaction subsystem typically is configured to retract the pivot arm within approximately 10 milliseconds, more preferably within approximately 5 milliseconds, and most preferably within approximately 1-2 milliseconds. Alternatively, the reaction subsystem may be configured to retract the pivot arm or other portion of the operative structure less quickly in some applications. For example, where the reaction subsystem is triggered in response to contact between the user's body and a guard structure proximate the blade, it may be sufficient to retract the pivot arm within 25, 50 or 100 milliseconds, etc.

Safety system 18 may be configured in a variety of different ways to retract either a portion or all of operative structure 12. Several exemplary embodiments of such safety systems, adapted for use on various types of power cutting machines, are described in U.S. Provisional Patent Application Serial No. 60/225,089, filed August 14, 2000 and U.S. Patent Application Serial No. 09/929,242, filed August 13, 2001, the disclosures of which are herein incorporated by reference. Additionally, Fig. 3 illustrates an exemplary miter saw 10 having an alternative

embodiment of safety system 18 configured to at least partially retract the pivot arm in the event of contact between the blade and the user's body.

Exemplary miter saw 10 includes a base assembly 90 adapted to support a workpiece (not shown) during cutting. Typically, one or more fences 92 are mounted on base assembly 90 and adapted to prevent the workpiece from shifting across the base assembly during cutting. Operative structure 12 is coupled to base assembly 90 and includes a platen 94, a tilt mechanism 96, and a pivot arm 98. Platen 94 is coupled to base assembly 90 and rotatable, relative to the base assembly, about the axis indicated at A. Tilt mechanism 96 is coupled to platen 94. At least a portion of the tilt mechanism is rotatable, relative to base assembly 90, about the axis indicated at B. Pivot arm 98 is coupled to tilt mechanism 96 and selectively pivotal toward and away from base assembly 90, as illustrated in Fig. 3. Typically, the pivot arm is biased upward away from base assembly 90 by a spring or other suitable mechanism.

Motor assembly 16 is mounted on pivot arm 98 and includes at least one motor 100 and a control handle 102. Blade 40 is coupled to an arbor shaft (not shown) that is rotatably driven by motor 100. Control handle 102 includes one or more controls (not shown) that are operable by a user to control motor 100. A user brings blade 40 into contact with a workpiece by grasping control handle 102 and pulling pivot arm 98 downward against the upward bias from a nominal position (indicated generally by dash lines in Fig. 3), toward base assembly 90. Once the cutting operation is completed, the user allows the pivot arm to pivot upward toward the nominal position.

It will be appreciated by those of skill in the art that the miter saw configuration depicted in Fig. 3 and described above is one commonly referred to as a "compound miter saw," which allows a user to make a compound (i.e., both mitered and beveled) cut in a workpiece by

adjusting the position of platen 94 and/or tilt mechanism 96. However, there are many other miter saw configurations known to those of skill in the art which are also suitable for use with the present invention. Thus, it will be understood that the particular miter saw configurations depicted and described herein are provided to illustrate exemplary embodiments of the invention, and should not be interpreted to limit the scope or application of the present invention.

Although not shown in Fig. 3, detection subsystem 22 and control subsystem 26 may be mounted at any desired location on miter saw 10 and configured to detect contact between blade 40 and a user's body as described above and in the references incorporated herein. Alternatively, the detection and control subsystems may be configured to detect contact between the user's body and some other portion of the miter saw such as a guard, etc. Upon receiving an activation signal, a first portion 104 of reaction subsystem 24 is configured to stop the rotation of blade 40, while a second portion 106 of the reaction subsystem is configured to move pivot arm 98 upward away from the base assembly. In the exemplary embodiment, first portion 104 includes a brake pawl 60 mounted in a cartridge 80, such as described above and in the incorporated references. Brake pawl 60 is selectively pivotal into blade 40 to stop the rotation of the blade. Alternatively, the first portion may employ other brake mechanisms such as described in the incorporated references. As a further alternative, first portion 104 may be omitted so that the rotation of blade 40 is not stopped in response to the occurrence of a dangerous condition.

In any event, second portion 106 retracts the pivot arm upward far enough to remove the blade from contact with the user's body. Preferably, the second portion is configured to move the pivot arm upward at least 1/8-inch, more preferably at least 1/4-inch, and most preferably at least 1/2-inch or more. In embodiments where the reaction subsystem is configured to stop the rotation of blade 40, the second portion preferably retracts the pivot arm before or at the same

time the blade is stopped. This prevents the pivot arm from moving downward as a result of angular momentum transferred to the pivot arm from the blade. The second portion of the reaction subsystem may be triggered prior to the first portion, or the second portion may be configured to engage the pivot arm more quickly than the brake pawl engages the blade.

5 Second portion 106 of exemplary reaction subsystem 24 includes a brace member 108 and a retraction assembly 110. Brace member 108 is pivotally coupled to tilt mechanism 96 at 105. Retraction assembly 110 is pivotally coupled to pivot arm 98 at 107 and configured to slidably receive at least a portion of brace member 108. The retraction assembly is configured to quickly grip or lock onto the brace member and urge the pivot arm upward upon receipt of an actuation signal from control subsystem 26. Once the retraction assembly has been triggered, pivot arm 98 is prevented from further downward movement toward base assembly 90. While second portion 106 is illustrated as having a single brace member and a single retraction assembly on one side of miter saw 10, it will be appreciated that the reaction subsystem may alternatively include a plurality of brace members and/or retraction assemblies positioned at selected locations on miter saw 10.

20 Brace member 108 may take any of a variety of different forms. In the exemplary embodiment, the brace member is an elongate bar or shaft pivotally coupled to tilt mechanism 96. Brace member 108 may be constructed of any suitably rigid material such as steel, aluminum, plastic, ceramic, etc. The pivotal coupling between the brace member and the tilt mechanism allows the brace member to pivot as necessary to follow the retraction assembly as the pivot arm moves toward and away from the base assembly. In the exemplary embodiment, the brace member is coupled to the tilt mechanism by a ball-joint-rod-end-bearing coupling 105, such as are available from a variety of sources including MSC Industrial Supply Company of

Melville, New York. Alternatively, other types of couplings may be used, such as universal couplings, etc.

In the exemplary embodiment, brace member 108 is coupled to an arm portion 112 of tilt mechanism 96 that extends outward from the tilt mechanism toward the base assembly. While arm 112 is depicted as an integral, unitary portion of the tilt mechanism, the arm portion may alternatively take the form of a separate bracket attached to the tilt mechanism. Alternatively, the arm may be omitted and brace member 108 may be coupled to another portion of the tilt mechanism. As further alternatives, the brace member may be coupled to a different portion of miter saw 10 such as platen 94, fence 92, or base assembly 90, etc. Embodiments of miter saw 10 and safety system 18 in which a brace member is coupled to other portions of the miter saw are described in more detail in U.S. Provisional Patent Application Serial No. 60/270,942, filed February 22, 2001 which has been incorporated herein by reference. In any event, the brace member should be relatively rigidly supported to ensure that pivot arm 98 is moved upward when retraction assembly 110 is triggered.

Retraction assembly 110 may be coupled to pivot arm 98 in any of a variety of different places. Typically, the retraction assembly and pivot point 107 are disposed to position brace member 108 spaced apart from pivot point 114 of arm 98 to increase the moment of the upward force applied by reaction subsystem 24 to pivot arm 98. It will be appreciated that the further brace member 108 is positioned from pivot point 114, the greater the moment of force provided by the retraction assembly. Thus, it is generally desirable, though not necessary, to position the brace member as close to the front of miter saw 10 (i.e., the left side as shown in Fig. 3) as possible without interfering with the use of the miter saw. Similarly, the pivot point 105 of the brace member is disposed, relative to the retraction assembly, to orient the brace member

generally perpendicular to the direction in which the pivot arm moves. This arrangement ensures that the downward force on the brace member is substantially a compression force rather than torque. Alternatively, retraction assembly 110 and pivot point 105 may be disposed at any selected positions suitable for stopping downward movement of pivot arm 98.

5 Since brace member 108 is coupled to tilt mechanism 96, the brace member will rotate along with pivot arm 98 about axis A when the miter saw is adjusted for mitered cuts. Similarly, the brace member will tilt about axis B when the miter saw is adjusted for beveled cuts. Thus, the exemplary configuration of reaction subsystem 24 depicted in Fig. 3 allows a user to adjust miter saw 10 throughout its full range of movement.

10 Optionally, reaction subsystem 24 may include one or more positioning mechanisms configured to remove any play or looseness in the couplings between brace member 108 and tilt mechanism 96, and/or the couplings between retraction assembly 110 and pivot arm 98. In situations where play or looseness may be present, the positioning mechanism ensures that the brace member and retraction assembly do not shift when the reaction subsystem is triggered. Examples of suitable positioning mechanisms are described in more detail in U.S. Provisional Patent Application Serial No. 60/270,942, filed February 22, 2001, which has been incorporated herein by reference. Alternatively, any other mechanism adapted to remove play from the reaction subsystem may be used.

15 Turning attention now to Figs. 4-8, one exemplary embodiment of retraction assembly 110 is illustrated. Exemplary retraction assembly 110 is configured to grip and push downward on brace member 108 to move pivot arm 98 upward in response to an activation signal from control subsystem 26. Retraction assembly 110 includes a housing 118 configured to slidably receive brace member 108. Housing 118 includes a lower wall 120, and an upper wall 122

spaced apart from the lower wall. Housing 118 also includes a first end wall 124 and a second end wall 126 extending between opposite ends of lower wall 120 and upper wall 122. The lower, upper and end walls are connected together by any suitable mechanism such as bolts 127. A pair of side walls 128 (shown in Fig. 3) cover the sides of the lower, upper and end walls to
5 enclose the housing.

Housing 118 is connected to the side of pivot arm 98 by a pivotal coupling 107 that allows the housing to move relative to the pivot arm as needed. Any of a variety of different couplings may be used which are known to those of skill in the art, such as a shoulder screw, etc. The pivotal coupling allows housing 118 to move as necessary to maintain a constant orientation or alignment with the brace member. In embodiments where the brace member is connected to a different structure on miter saw 10 such as platen 94 or fence 92, coupling 107 may be configured to allow the housing to both pivot parallel to the side of the pivot arm and tilt away from the pivot arm as needed.

As mentioned above, housing 118 is configured to slide along brace member 108. Lower wall portion 120 includes an orifice 130 configured to slide over the brace member. Similarly, upper wall portion 122 includes an orifice 132 configured to slide over the brace member. Orifices 130 and 132 are generally axially aligned and sized to closely fit around the brace member, thereby maintaining the housing in a uniform orientation relative to the brace member as pivot arm 98 is moved toward and away from the workpiece.

Retraction assembly 110 also includes an actuator 134 configured to selectively grip brace member 108 and push the housing upward. Actuator 134 may be any one or a combination of elements, devices or mechanisms configured to quickly and securely grip the brace member. In the exemplary embodiment, actuator 134 includes a clamping device 136 adapted to
20

selectively grip the brace member, and a drive mechanism 138 adapted to urge the housing upward relative to the clamping device. Clamping device 136 is formed to define an orifice 140 adapted to closely fit and slide along the brace member. The clamping device is pivotal between a nominal or unactuated position (as shown in Figs. 4 and 5), and an actuated or locked position (as shown in Fig. 7). When the clamping device is in the nominal position, the sides of orifice 140 are substantially aligned with the sides of brace member 108 so that the clamping device slides relatively freely along the brace member. Conversely, when the clamping device is pivoted into the locked or actuated position, the sides of orifice 140 press into and bind against the brace member to releasably lock the clamping device onto the brace member. Drive mechanism 138 is disposed between the clamping device and upper wall 122 and configured to push the upper wall away from the clamping device when the clamping device is in the locked position. As a result, housing 118 and pivot arm 98 are pushed upward relative to the brace member and base assembly 90.

Clamping device 136 may be constructed of any suitable material adapted to grip the brace member and support the force exerted by drive mechanism 138. Typically, the clamping device is constructed of a material which does not cause damage to brace member 108 when the retraction assembly is triggered. For example, the clamping device and brace member may each be formed from a relatively rigid material such as hardened steel. Alternatively, the clamping device and/or brace member may be formed of any of a variety of other suitable materials known to those of skill in the art.

When in the nominal position, clamping device 136 is disposed adjacent the lower surface of upper wall 122 between end walls 124 and 126. The end walls are spaced to align the clamping device and orifice 140 end-to-end with the upper wall and orifice 132. Each end wall

is inwardly tapered adjacent the upper wall so as not to obstruct the movement of the clamping device. Upper wall 122 includes a pair of alignment structures 142 adapted to align the clamping device and orifice 140 side-to-side with the upper wall and orifice 132. When clamping device 136 is in the nominal position, orifice 140 is generally axially aligned with orifice 132 and orifice 130 to slidably receive the brace member.

Clamping device 136 is held in the nominal position by a yieldable support element such as spring 144 that engages the clamping device adjacent a first end 146, as well as a releasable restraining mechanism 148 that engages the clamping device adjacent a second end 150. First end wall 124 includes a recessed region adapted to hold a portion of spring 144 and align the spring with the clamping device. Although spring 144 is depicted as a compression spring, it will be appreciated that spring 144 may be any type of spring or other mechanism adapted to yieldably hold first end 146 adjacent the lower surface of upper wall 122.

Restraining mechanism 148 may take any of a variety of different configurations adapted to releasably support second end 150 of the clamping device. In the exemplary embodiment, drive mechanism 138 (which will be discussed in more detail below) exerts a constant downward force on the clamping device adjacent second end 150. Restraining mechanism 148 is configured to support the clamping device against the force exerted by the drive mechanism. Typically, though not necessarily, the restraining mechanism is generally aligned with the drive mechanism to reduce any bending stress to the clamping device.

Exemplary restraining mechanism 148 is selectively collapsible to release the second end of the clamping device. The restraining mechanism includes an elongate collapsible base 154 adapted to support an elongate brace 156. In its uncollapsed state illustrated in Figs. 4-6, a lower end 158 of base 154 rests on the upper surface of lower wall 120. The base extends upward from

the lower wall toward the clamping device. A lower end 160 of brace 156 rests on an upper end 162 of base 154. The brace extends upward from the base to support the clamping device. When the base collapses, the brace is dislodged, thereby releasing the clamping device as shown in Figs. 7-8.

5 When in the uncollapsed, upright position, one side of base 154 is disposed against a buttress structure 164. One side of lower end 160 of the brace is also disposed against the buttress structure, while an upper end 166 of the brace is disposed against a shoulder structure 168 on the clamping device. Shoulder structure 168 is configured to position the brace in upright alignment on top of the base. Base 154 and brace 156 are clamped against the buttress structure by a stabilizer member 170. The stabilizer member is held in clamping engagement with the base and the brace by a fusible member 70 such as described above and in the incorporated references. Fusible member 70 extends from the stabilizer member, over a contact mount 72 to an anchor point 172. Contact mount 72 is coupled to a firing subsystem (not shown) adapted to supply sufficient electrical current to melt the fusible member. In the exemplary embodiment, contact mount 72 is anchored to buttress structure 164, which is constructed of an electrically non-conducting material such as plastic, etc.

Lower end 158 of the base includes a beveled region 174 opposite the buttress structure. As shown in Fig. 6, beveled region 174 extends through more than half the thickness of the base. Lower end 160 of the brace includes a beveled region 176 adjacent the buttress structure. As a
20 result, a portion of the downward pressure exerted on the clamping device by the drive mechanism is translated onto upper end 162 as a pivoting force away from the buttress structure. The remainder of the downward force is translated into a downward force on lower wall 128.

The upper end of the base is prevented from pivoting outward so long as stabilizer structure 170 remains in place.

Those of skill in the art will appreciate that the particular configuration of restraining mechanism 148 described above provides a mechanical advantage for supporting second end 150 of the clamping device under the downward force of the drive mechanism. The proportion of downward force translated into pivoting force on the base will vary with the depth of beveled regions 174 and 176. Beveled regions 174 and 176 typically are configured so that much of the downward force applied by the drive mechanism is translated into downward force on base 154 rather than pivoting force. As a result, fusible member 70 is only required to support a portion of the force exerted by the drive mechanism. Indeed, several hundred pounds of downward force may be translated into only 10-20 pounds of outward pivoting force on stabilizer structure 170. This allows the fusible member to have a smaller diameter, thereby requiring less energy to melt. Nevertheless, the outward pivoting force should be sufficient to ensure the base collapses within 5-10 milliseconds, and preferably within 1-5 milliseconds.

In any event, when stabilizer member 170 is released, the upper end of base 154 quickly pivots outward from the buttress structure and collapses beneath the brace, as illustrated in Figs. 6 and 7. Upper end 166 of the brace includes a beveled region 178 opposite shoulder structure 168 to allow the lower end of the brace to freely pivot outward from the buttress structure along with the base. Second end 150 of the clamping device is thereby released to move downward under the urging of the drive mechanism.

While second end 150 of the clamping device is pushed downward by the drive mechanism, first end 146 is pushed upward by spring 144. As a result, clamping device 136 pivots about brace member 108 into the locked position where the edges of orifice 140 bind

against the sides of the brace member as shown in Fig. 7. The angle through which the clamping device must pivot before binding against the brace member will vary based at least partially on the size differential between orifice 140 and brace member 108. It is believed that the binding force generated by the clamping device against the brace member is increased where the pivot angle between the nominal position and the locked position is relatively small. Therefore, orifice 140 typically is sized to fit relatively closely around the brace member. For example, in an embodiment where brace member 108 takes the form of a rod having a circular cross-section with a diameter of approximately 0.375-inch, one suitable diameter for orifice 140 would be approximately 0.376-inch. Alternatively, other diameters may also be used within the scope of the invention. For clarity, the size difference between orifice 140 and brace member 108 is shown substantially exaggerated in Figs. 5, 7 and 8.

As mentioned above, drive mechanism 138 is disposed between upper wall 122 and second end 150 of the clamping device. The drive mechanism is configured to urge the second end and upper wall apart when the clamping device is released from restraining mechanism 148. Once clamping device 136 pivots to the locked position, further downward movement of second end 150 is prevented because the clamping device is locked against the brace member. As a result, the additional drive force exerted by the drive mechanism forces upper wall 122 and housing 118 upward relative to the clamping device and brace member, as illustrated in Fig. 8. Since the housing is coupled to pivot arm 98, the pivot arm is forced upward as well.

Drive mechanism 138 should be configured to overcome the downward momentum of the pivot arm as well as any transferred angular momentum caused by stopping blade 40. In addition, the upward force exerted by the drive mechanism on the housing should be substantially larger than any downward force exerted by spring 144. Typically, the drive

mechanism is configured to provide 100-500 pounds of upward force on the pivot arm. The length of upward travel of the pivot arm will depend on the length of translation, or 'throw,' of the drive mechanism as well as the distance second end 150 pivots downward before locking against the brace member.

5 In the exemplary embodiment, drive mechanism 138 includes a plurality of Belleville springs 180 stacked in series. The number of springs in the series is selected to provide a desired throw. Optionally, each spring in the series may alternatively be plural springs stacked in parallel to provide a desired amount of driving force. Springs 180 are disposed in a recessed region 182 of upper wall 122. The recessed region is sized to maintain the springs in general axial alignment. Additionally, clamping device 136 includes a spindle structure 183, adapted to fit within the central bores of at least a portion of the springs to maintain alignment between the springs. The spindle structure also serves to maintain alignment between the springs and the clamping device. It will be appreciated by those of skill in the art that drive mechanism 138 may alternatively take any of a variety of other configurations adapted to lock the clamping device against the brace member and force the pivot arm upward. For example, the drive mechanism may include a coil compression spring, explosive device, etc.

In any event, once the retraction assembly has been triggered, it may be uncoupled from the pivot arm and slid off the brace member. A new, untriggered retraction assembly may then be installed to place miter saw 10 and safety system 18 back in operation. Alternatively, the triggered retraction assembly may be reset using a new fusible member.

While one particular implementation of retraction assembly 110 has been described, it will be appreciated that numerous alterations and modifications are possible within the scope of the invention. Additionally, while the retraction assembly has been described in the context of

retracting the pivot arm of a miter saw, it will be appreciated that the retraction assembly may also be adapted for use in other ways and on other machines. For example, Fig. 9 illustrates another embodiment of safety system 18 in the context of a radial arm saw 184. Typically, radial arm saw 184 includes a horizontal base 186, a vertical support column 188 extending upward
5 from base 186, and a guide arm 190 which extends from column 188 vertically spaced above base 186. Carriage assembly 192 is slidably coupled to the underside of guide arm 190. Carriage assembly 192 is connected to a saw housing 194 and motor assembly 16, allowing blade 40 to be pulled across the base to cut workpieces (not shown) supported on the base.

Carriage assembly 192 includes an upper section 196 slidably coupled to guide arm 190, and a lower section 198 attached to housing 194 and/or motor assembly 16. Lower section 198 is coupled to slide vertically on a plurality (e.g., four) of shafts 200 that extend downward from upper section 196. Shafts 200 pass through holes in the lower section and are received into end caps 202 adapted to prevent the lower section from sliding off the shafts. During normal operation, the weight of housing 194, motor assembly 16, blade 40, etc., maintain the lower section of carriage assembly 192 resting on end caps 202 and spaced apart from the upper section.

Reaction subsystem 24 includes a brace member 108, such as described above, mounted on upper section 196 to extend downward toward lower section 198. The reaction subsystem also includes a retraction assembly 110, such as described above, mounted on lower section 198
20 to receive a portion of the brace member. Upon receiving an activation signal from control subsystem 26 (not shown), retraction assembly 110 is configured to quickly clamp onto brace member 108 and force lower section 198 upward. Thus, blade 40 is retracted upward upon the occurrence of a dangerous condition such as contact between the user's body and the blade.

Optionally, reaction subsystem 24 may also include a brake mechanism 28 configured to stop the rotation of the blade. In an alternative embodiment, retraction assembly 110 may be configured to reverse the forward and/or rearward translation of carriage assembly 192 along guide arm 190.

5 Figure 10 illustrates another alternative configuration of safety system 18 for use on a pneumatic up-cut chop saw 204. Chop saw 204 includes a blade 40 mounted to a pivotal arbor block 206. Upon activation of a switch by the user, the arbor block is pivoted to the upward position shown in the dashed lines by a pneumatic cylinder 208. Blade 40 extends through a top plate 210 of the saw to cut a workpiece (not shown) resting on the top plate. Although not shown, chop saw 204 may include one or more vise/guards mounted on top plate 210 to hold down the workpiece. As described in more detail in U.S. Provisional Patent Application Serial No. 60/233,459, filed September 18, 2000 and U.S. Patent Application Serial No. 09/955,418, filed September 17, 2001, the disclosures of which are herein incorporated by reference, safety system 18 may be configured to trigger reaction subsystem 24 in response to contact between the user's body and one or more of the blade, the top plate, the vise/guard, etc.

As shown in Fig. 10, exemplary reaction subsystem 24 includes a brace member 108, such as described above, pivotally anchored to top plate 210 or some other suitable portion of the chop saw. The reaction subsystem also includes a retraction assembly 110, such as described above, adapted to receive and slide along the brace member. Retraction assembly 110 is coupled
20 to arbor block 206 by a linkage 212.

During normal operation, the retraction assembly slides up and down the brace member as the pneumatic cylinder is actuated to raise and lower the blade. Upon receiving an activation signal from control subsystem 26 (not shown), the retraction assembly is configured to clamp

onto the brace member and force arbor block 206 downward. Typically, safety system 18 will simultaneously reverse the pressure of the pneumatic cylinder. However, reversing the pressure of the pneumatic cylinder is usually too slow to prevent injury if the dangerous condition that was detected is contact between the user's body and the blade. Therefore, retraction assembly 110 typically is configured to exert sufficient downward force to overcome the upward force of the pneumatic cylinder. In addition, linkage 212 typically may be configured to ensure that the force exerted by the retraction assembly has a greater moment than the force exerted by the pneumatic cylinder. Alternative configurations of the pneumatic up-cut chop saw, including alternative linkages, are described in more detail in the incorporated references.

As described above, the present invention provides a miter saw which is substantially safer than existing saws. The miter saw includes a safety system 18 adapted to detect the occurrence of a dangerous condition and at least partially retract the pivot arm to prevent serious injury to a user. Those of skill in the art will appreciate that many modifications and variations to the exemplary embodiments are possible within the scope of the invention. Furthermore, the safety system may be adapted for use on a variety of other saws in addition to miter saws as has been described above. Additional modifications and variations, as well as such other saws are described in more detail in the following references, the disclosures of which are herein incorporated by reference: PCT Patent Application Serial No. PCT/US00/26812, filed September 29, 2000; U.S. Provisional Patent Application Serial No. 60/225,212, filed August 14, 2000; U.S. Provisional Patent Application Serial No. 60/225,210, filed August 14, 2000; U.S. Provisional Patent Application Serial No. 60/225,201, filed August 14, 2000; U.S. Provisional Patent Application Serial No. 60/225,058, filed August 14, 2000; U.S. Provisional Patent Application Serial No. 60/225,057, filed

August 14, 2000; and U.S. Provisional Patent Application Serial No. 60/157,340, filed October 1, 1999.

It is believed that the disclosure set forth above encompasses multiple distinct inventions with independent utility. While each of these inventions has been disclosed in its preferred form,
5 the specific embodiments thereof as disclosed and illustrated herein are not to be considered in a limiting sense as numerous variations are possible. The subject matter of the inventions includes all novel and non-obvious combinations and subcombinations of the various elements, features, functions and/or properties disclosed herein. No single feature, function, element or property of the disclosed embodiments is essential to all of the disclosed inventions. Similarly, where the claims recite "a" or "a first" element or the equivalent thereof, such claims should be understood to include incorporation of one or more such elements, neither requiring nor excluding two or more such elements.

It is believed that the following claims particularly point out certain combinations and subcombinations that are directed to one of the disclosed inventions and are novel and non-obvious. Inventions embodied in other combinations and subcombinations of features, functions, elements and/or properties may be claimed through amendment of the present claims or presentation of new claims in this or a related application. Such amended or new claims, whether they are directed to a different invention or directed to the same invention, whether different, broader, narrower or equal in scope to the original claims, are also regarded as included within
20 the subject matter of the inventions of the present disclosure.